

# Add server

## Docker Immich module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#) | [n8n](#)

Add a new server to the system WHMCS.

System Settings->Servers->Add New Server

- Enter the correct **Name** and **Hostname**

Name	<input type="text" value="d01-test.uuq.pl"/>
Hostname	<input type="text" value="d01-test.uuq.pl"/>
IP Address	<input type="text"/>
Assigned IP Addresses (One per line)	<div></div>
Monthly Cost	<input type="text" value="0.00"/>
Datacenter/NOC	<input type="text"/>
Maximum No. of Accounts	<input type="text" value="200"/>
Server Status Address	<div><input type="text"/> To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. https://www.example.com/status/</div>
Enable/Disable	<input type="checkbox"/> Check to disable this server

**Attention: Important Information**

The **hostname** field represents the actual domain of the server running Docker and must match the **server\_domain** parameter in the **n8n workflow**. If they do not match, communication will not function correctly.

Additionally, this domain must be configured so that all its subdomains resolve to the IP address of the server running Docker.

**Parameters** Test step

**Parameters** Settings Docs

Mode

Manual Mapping

Fields to Set

server\_domain

A String

d01-test.uuq.pl

[empty]

clients\_dir

A String

/opt/docker/clients

[empty]

In the **Server Details** section, select the **"PUQ Docker Immich"** module and enter the correct **username** and **password** for the **API endpoint** in the n8n workflow.

Additionally, in the **Access Hash** field, insert the **URL of the API entry point** for the n8n workflow.

Server Details

Module	<div>PUQ Docker Immich</div> <div>Test Connection</div> <div>✓ Connection successful. Some values have been auto-filled.</div>
Username	<div>Immich</div>
Password	<div>....</div>
Access Hash	<div>https://n8n.puqcloud.com/webhook/docker-immich</div>
Secure	<div><input checked="" type="checkbox"/> Check to use SSL Mode for Connections</div>

## Webhook URLs

Test URL

Production URL

POST

<https://n8n.puqcloud.com/webhook/docker-immich>

## HTTP Methods

POST [×](#)

## Path

docker-immich

## Authentication

Basic Auth [×](#)

## Credential for Basic Auth

Immich [×](#)

## Respond

Using 'Respond to Webhook' Node [×](#)

Insert a 'Respond to Webhook' node to control when and how you respond. [More details](#)

## Options

No properties

Add option [×](#)

---

Revision #2

Created 18 March 2025 18:55:06 by Ruslan

Updated 21 March 2025 14:40:44 by Yuliia Noha