PUQ Mautic Image not found or type unknown

Installation and configuration guide

- Basic concepts and requirements
- WHMCS setup (install/update)
- Preparing Docker Server
- Setting up n8n workflow
- Add server
- Product Configuration
- Metric Billing
- Email Template (puqDockerInfluxDB Welcome Email)
- Email Template (puqDockerInfluxDB Update Email)
- Email Template (puqDockerInfluxDB Notification disk limit)

Basic concepts and requirements

Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

> Before you start, it is important to read and familiarize yourself with the following articles at this link:
>
> https://doc.puq.info/books/docker-modules

The **WHMCS Docker InfluxDB module** is part of the **WHMCS Docker module series** developed by **PUQcloud**. This module enables service providers to offer **InfluxDB Docker containers** as a service to their clients, allowing for seamless automation and integration.

The system consists of three core components:

WHMCS Module

The **core component**, installed in WHMCS, manages service provisioning and automation from the WHMCS side.

Debian 12 Server

A server running **Debian 12** with the following pre-installed:
Docker – For container management

We have prepared instructions for installing and configuring Docker

https://doc.puq.info/books/docker-modules/page/installing-docker-for-puqcloud-modules

n8n Server

This server facilitates communication between the WHMCS module and the Docker server, ensuring smooth workflow execution.

To explore n8n’s full potential, visit the **official n8n website** for documentation, tutorials, and community support.

Key Features & Concepts

⚙ Workflow Automation

n8n provides a **graphical workflow builder**, allowing users to automate various tasks, such as:
✔ **Sending notifications**
✔ **Configuring firewalls** on external routers
✔ **Managing DNS settings**
✔ **Custom automation processes** tailored to specific needs

□□ Flexibility & Customization

The module offers **personalized settings** and supports **elastic automation**, giving clients full control over their n8n workflows.

WHMCS setup (install/update)

Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

> **Module is coded ionCube v13**

Supported php version:

- php 7.4 WHMCS 8.11.0 -
- php 8.1 WHMCS 8.11.0 +
- php 8.2 WHMCS 8.11.0 +

> To install and update a module, you must perform one and the same action.

1. Download the latest version of the module.

PHP 8.2

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Docker-InfluxDB/php82/PUQ_WHMCS-Docker-InfluxDB-latest.zip
```

PHP 8.1

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Docker-InfluxDB/php81/PUQ_WHMCS-Docker-InfluxDB-latest.zip
```

PHP 7.4

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Docker-InfluxDB/php74/PUQ_WHMCS-Docker-InfluxDB-latest.zip
```

> All versions are available via link:
> https://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Docker-InfluxDB/

2. Unzip the archive with the module.

```
unzip PUQ_WHMCS-Docker-InfluxDB-latest.zip
```

3. Copy and Replace "puqDockerInfluxDB" from "PUQ_WHMCS-Docker-InfluxDB" to "WHMCS_WEB_DIR/modules/servers/"

Preparing Docker Server

Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

To install the Docker server for this module, please follow the instructions at the following link:

https://doc.puq.info/books/docker-modules/page/installing-docker-for-puqcloud-modules

Setting up n8n workflow

Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

Overview

The **Docker InfluxDB WHMCS module** uses a specially designed workflow for **n8n** to automate deployment processes. The workflow provides an API interface for the module, receives specific commands, and connects via SSH to a server with Docker installed to perform predefined actions.

Prerequisites

- You must have your own **n8n** server.
- Alternatively, you can use the official **n8n** cloud installations available at: n8n Official Site

Installation Steps

Install the Required Workflow on n8n


You have two options:

Option 1: Use the Latest Version from the n8n Marketplace


- The latest workflow templates for our modules are available on the official n8n marketplace.
- Visit our profile to access all available templates: PUQcloud on n8n

Option 2: Manual Installation

- Each module version comes with a workflow template file.




- You need to manually import this template into your n8n server.





n8n Workflow API Backend Setup for WHMCS/WISECP

Configure API Webhook and SSH Access


- Create a **Basic Auth Credential** for the Webhook API Block in n8n.



Additional Resources
• Full documentation: https://doc.puq.info/books/docker-influxdb-whmcs-module
• WHMCS module: https://puqcloud.com/whmcs-module-docker-influxdb.php
POST
API
Parametrs
manual
If
true
false



API
Listen for test event
Parameters
Settings
Docs
Webhook URLs
Test URL
Production URL
POST
https://n8n.puqcloud.com/webhook-test/docke
r-influxdb
HTTP Methods
POST
Path
docker-influxdb
Authentication
Basic Auth
Credential for Basic Auth
InfluxDB
Basic Auth
Immich
Basic Auth
InfluxDB
Basic Auth
MinIO
Basic Auth
n8n
Basic Auth
Vaultwarden
Basic Auth
+ Create new credential



- Create an **SSH Credential** for accessing a server with Docker installed.






SSH
Test step
Parameters
Settings
Docs
Credential to connect with
d01-test.uuq.pl-puq
d01-test.uuq.pl-puq
SSH Password
+ Create new credential
Execute
Command
{{ $json.sh }}
Working Directory
/
/



Modify Template Parameters

In the **Parameters** block of the template, update the following settings:





- `server_domain` – Must match the domain of the WHMCS/WISECP Docker server.
- `clients_dir` – Directory where user data related to Docker and disks will be stored.
- `mount_dir` – Default mount point for the container disk (recommended not to change).


Do not modify the following technical parameters:

- `screen_left`
- `screen_right`

Deploy-docker-compose

In the **Deploy-docker-compose** element, you have the ability to modify the Docker Compose configuration, which will be generated in the following scenarios:

- When the service is created
- When the service is unlocked
- When the service is updated



```
name: "{{ $('API').item.json.body.domain }}_influxdb"


services:
  {{ $('API').item.json.body.domain }}_influxdb:
    container_name: {{ $('API').item.json.body.domain }}_influxdb
    image: influxdb:2.7
    restart: unless-stopped
    volumes:
      - {{ $('Parametrs').item.json.mount_dir }}/{{ $('API').item.json.body.domain }}/lib:/var/
lib/influxdb2
      - {{ $('Parametrs').item.json.mount_dir }}/{{ $('API').item.json.body.domain }}/etc:/etc/
influxdb2
    environment:
      - LETSENCRYPT_HOST={{ $('API').item.json.body.domain }}
      - VIRTUAL_HOST={{ $('API').item.json.body.domain }}
      - DOCKER_INFLUXDB_INIT_MODE=setup
      - DOCKER_INFLUXDB_INIT_USERNAME={{ $('API').item.json.body.username }}
      - DOCKER_INFLUXDB_INIT_PASSWORD={{ $('API').item.json.body.password }}
      - DOCKER_INFLUXDB_INIT_ORG={{ $('API').item.json.body.username }}_ORG
      - DOCKER_INFLUXDB_INIT_BUCKET={{ $('API').item.json.body.username }}_BUCKET
    healthcheck:
      disable: false
    networks:
      - nginx-proxy_web
    mem_limit: "{{ $('API').item.json.body.ram }}G"
    cpus: "{{ $('API').item.json.body.cpu }}"

networks:
  nginx-proxy_web:
    external: true
```

nginx

In the **nginx** element, you can modify the configuration parameters of the web interface proxy server.

- The **main** section allows you to add custom parameters to the **server** block in the proxy server configuration file.
- The **main_location** section contains settings that will be added to the **location /** block of the proxy server configuration. Here, you can define custom headers and other parameters specific to the root location.



nginx

Test step

Parameters | Settings | Docs

Mode

Manual Mapping

Fields to Set

main | A String | =

[empty]

main_location | A String | =

```
proxy_pass_header Server;
proxy_set_header X-Real-IP $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
proxy_set_header X-Scheme $scheme;
proxy_set_header Host $http_host;
```

proxy_pass_header Server; proxy_set_header X-Real-IP $remote_addr; proxy_set_he...

Drag input fields here or Add Field

Include Other Input Fields

Options


No properties

Add option

Bash Scripts

Management of Docker containers and all related procedures on the server is carried out by executing Bash scripts generated in **n8n**. These scripts return either a JSON response or a string.

- All scripts are located in elements directly connected to the **SSH** element.
- You have full control over any script and can modify or execute it as needed.


-docker-compose
manual
Service Actions
mode: Rules
Test Connection1
manual
Deploy
manual
Suspend
manual
Unsuspend
manual
Terminated
manual
ChangePackage
manual
Inspect
manual
Stat
manual
Log
manual
Start
manual
Stop
manual
Mount Disk
manual
Unmount Disk
manual
GET ACL
manual
SSH
execute command

Add server


Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

Add a new server to the system WHMCS.


```
System Settings->Servers->Add New Server
```

- Enter the correct **Name** and **Hostname**



Attention: Important Information


The **hostname** field represents the actual domain of the server running Docker and must match the **server_domain** parameter in the **n8n workflow**. If they do not match, communication will not function correctly.
Additionally, this domain must be configured so that all its subdomains resolve to the IP address of the server running Docker.




In the **Server Details** section, select the **"PUQ Docker InfluxDB"** module and enter the correct **username** and **password** for the **API endpoint** in the n8n workflow.

Additionally, in the **Access Hash** field, insert the **URL of the API entry point** for the n8n workflow.

Server Details

Module	PUQ Docker InfluxDB  Test Connection ✔ Connection successful. Some values have been auto-filled.
Username	InfluxDB
Password	••••
Access Hash	https://n8n.puqcloud.com/webhook/docker-influxdb
Secure	☑ Check to use SSL Mode for Connections


API
Listen for test event
Parameters
Settings
Docs
Webhook URLs
Test URL
Production URL
POST
https://n8n.puqcloud.com/webhook/docker-influxdb
HTTP Methods
POST
Path
docker-influxdb
Authentication
Basic Auth
Credential for Basic Auth
InfluxDB
Respond
Using 'Respond to Webhook' Node
Insert a 'Respond to Webhook' node to control when and how you respond. More details
Options
No properties
Add option

Product Configuration

Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

Add new product to WHMCS

```
System Settings->Products/Services->Create a New Product
```

In the **Module settings** section, select the **"PUQ Docker InfluxDB"** module


- **License key –** A pre-purchased license key for the **"PUQ Docker InfluxDB"** module. For the module to work correctly, the key must be active
- **Disk space** – defines the allocated disk size for the Docker container.
- **CPU** – sets the CPU usage limit for the Docker container.
- **RAM** – specifies the amount of RAM allocated to the Docker container.
- **Link to instruction** – URL to a guide that will be displayed in the client panel if provided.
- **Main domain** – defines the primary domain for the web interface of the application. If not set, the main domain will be taken from the **hostname** parameter in the server settings.
- **Subdomain** – a personal subdomain assigned to each service. If left empty or if the subdomain is already taken, it will be automatically generated in the format **{user_id}-{service_id}**.
-

Supported Macros for **App Subdomain**:

  - **{user_id}** – Client ID
  - **{service_id}** – Service ID
  - **{random_digit_x}** – Random number (x defines the length)
  - **{random_letter_x}** – Random letter (x defines the length)
  - **{unixtime}** – Unix timestamp
  - **{year}, {month}, {day}, {hour}, {minute}, {second}** – Date and time values
- **Notification, used disk space X %** – The percentage value that sets the threshold for the container's disk space usage will trigger a notification message to the client once the

threshold is reached.

- **Notification disk limit email template** – The email template for the notification that will be sent when the threshold is reached.



Metric Billing


Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

To bill certain metrics separately, you can use the standard WHMCS Metric Billing mechanism.

To configure it, you need to enable the required metrics and set the desired prices. Metrics work based on the standard WHMCS mechanism, the description of which can be found here:

https://docs.whmcs.com/products/configuration-options/usage-billing/



Configure Pricing

Traffic IN (GB)

Metric Type: Monthly

Metric Unit: GigaBytes

Pricing

Scheme:

(•) Per Unit ⓘ ( ) Total Volume ⓘ ( ) Graduated ⓘ

Quantity Included

0.00

Price Per GB			
PLN	EUR	UAH	USD
1.00	1.00	1.00	1.00

Close Save

Email Template (puqDockerInfluxDB Welcome Email)


Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

Create an email template for customer notifications.

```
System Settings->Email Templates->Create New Email Template
```

- **Email Type:** Product/service
- **Unique Name:** puqDockerInfluxDB Welcome Email



Subject:

```
InfluxDB Order Information
```

Body:

```
Dear {$client_name},

Your order has been accepted for implementation.

Product/Service: {$service_product_name}
Payment Method: {$service_payment_method}
Amount: {$service_recurring_amount}
Billing Cycle: {$service_billing_cycle}
Next Due Date: {$service_next_due_date}


The installation and setup of your InfluxDB instance is in progress.
Within the next 4-5 minutes, you will be able to use your InfluxDB instance.

Upon your first login, you will need to create an account.

Here is the link to your InfluxDB server.

https://{$service_domain}/

Thank you for choosing us.

{$signature}
```

Subject: InfluxDB Order Information

File Edit View Insert Format Table Help

Paragraph Verdana 11pt

Dear **{$client_name}**,

Your order has been accepted for implementation.

Product/Service: **{$service_product_name}**
Payment Method: **{$service_payment_method}**
Amount: **{$service_recurring_amount}**
Billing Cycle: **{$service_billing_cycle}**
Next Due Date: **{$service_next_due_date}**

The installation and setup of your InfluxDB instance is in progress.
Within the next 4-5 minutes, you will be able to use your InfluxDB instance.

Upon your first login, you will need to create an account.

Here is the link to your InfluxDB server.

https://{$service_domain}/

Thank you for choosing us.

{$signature}

P

82 WORDS POWERED BY TINYMCE

Email Template (puqDockerInfluxDB Update Email)


Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

Create an email template for customer notifications.

```
System Settings->Email Templates->Create New Email Template
```

- **Email Type:** Product/service
- **Unique Name:** puqDockerInfluxDB Update Email



Subject:

```
InfluxDB Update Information
```

Body:

```
Dear {$client_name},


Your instance is currently being updated.
You will be able to use your InfluxDB server again within 3 minutes.


Here is the link to your InfluxDB server.


https://{$service_domain}/
Thank you for choosing us.


{$signature}
```

Subject: InfluxDB Update Information

File Edit View Insert Format Table Help

Paragraph Verdana 11pt

Dear **{$client_name},**

Your instance is currently being updated.
You will be able to use your InfluxDB server again within 3 minutes.

Here is the link to your InfluxDB server.

https://{$service_domain}/
Thank you for choosing us.

{$signature}

P 38 WORDS POWERED BY TINYMCE

Email Template (puqDockerInfluxDB Notification disk limit)


Docker InfluxDB module **WHMCS**

Order now | Download | FAQ | n8n

Create an email template for customer notifications.

```
System Settings->Email Templates->Create New Email Template
```

- **Email Type:** Product/service
- **Unique Name:** puqDockerInfluxDB Notification disk limit



Subject:

```
Disk space usage {$disk_used_percentage}%
```

Body:

```
Dear {$client_name},

We want to inform you that your InfluxDB service is running low on disk space.
Please take action to prevent service interruptions.

Service Details:

Product/Service: {$service_product_name}
Domain: {$service_domain}
Total Disk Space: {$disk_total}
Used Disk Space: {$disk_used} ({$disk_used_percentage}%)
Consider freeing up space or upgrading your plan if needed.

{$signature}
```

Subject: Disk space usage {$disk_used_percentage}%

File Edit View Insert Format Table Help

Paragraph Verdana 11pt

Dear {$client_name},

We want to inform you that your InfluxDB service is running low on disk space.
Please take action to prevent service interruptions.

Service Details:

Product/Service: {$service_product_name}
Domain: {$service_domain}
Total Disk Space: {$disk_total}
Used Disk Space: {$disk_used} ({$disk_used_percentage}%)
Consider freeing up space or upgrading your plan if needed.

{$signature}

P 58 WORDS POWERED BY TINYMCE