

Add server

Docker MinIO module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#) | [n8n](#)

Add a new server to the system WHMCS.

System Settings->Servers->Add New Server

- Enter the correct **Name** and **Hostname**

Name	<input type="text" value="d01-test.uuq.pl"/>
Hostname	<input type="text" value="d01-test.uuq.pl"/>
IP Address	<input type="text"/>
Assigned IP Addresses (One per line)	<div></div>
Monthly Cost	<input type="text" value="0.00"/>
Datacenter/NOC	<input type="text"/>
Maximum No. of Accounts	<input type="text" value="200"/>
Server Status Address	<div><input type="text"/> To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. https://www.example.com/status/</div>
Enable/Disable	<input type="checkbox"/> Check to disable this server

Attention: Important Information

The **hostname** field represents the actual domain of the server running Docker and must match the **server_domain** parameter in the **n8n workflow**. If they do not match, communication will not function correctly.

Additionally, this domain must be configured so that all its subdomains resolve to the IP address of the server running Docker.

Parameters Test step

Parameters Settings Docs

Mode

Manual Mapping

Fields to Set

server_domain

A String

d01-test.uuq.pl

[empty]

clients_dir

A String

/opt/docker/clients


[empty]


In the **Server Details** section, select the **"PUQ Docker MinIO"** module and enter the correct **username** and **password** for the **API endpoint** in the n8n workflow.

Additionally, in the **Access Hash** field, insert the **URL of the API entry point** for the n8n workflow.

Server Details


Module	<div>PUQ Docker MinIO</div> <div>Test Connection</div> <div>✓ Connection successful. Some values have been auto-filled.</div>
Username	<div>minio</div>
Password	<div>....</div>
Access Hash	<div>https://n8n.puqcloud.com/webhook/docker-minio</div>
Secure	<div><input checked="" type="checkbox"/> Check to use SSL Mode for Connections</div>

 API



Parameters

Settings

Docs 

Webhook URLs


Test URL


Production URL

POST

https://n8n.puqcloud.com/webhook/docker-minio

HTTP Methods

POST 




Path

docker-minio


Authentication


Basic Auth



Credential for Basic Auth


Incom API User





Respond

Using 'Respond to Webhook' Node




Insert a 'Respond to Webhook' node to control when and how you respond. [More details](#)

Options

No properties

Add option



Revision #2

Created 14 March 2025 17:54:10 by Ruslan

Updated 21 March 2025 14:22:14 by Yuliia Noha