

# Add server

## Docker MinIO module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#) | [n8n](#)

Add a new server to the system WHMCS.

System Settings->Servers->Add New Server

- Enter the correct **Name** and **Hostname**

Name	<input type="text" value="d01-test.uuq.pl"/>
Hostname	<input type="text" value="d01-test.uuq.pl"/>
IP Address	<input type="text"/>
Assigned IP Addresses (One per line)	<input type="text"/>
Monthly Cost	<input type="text" value="0.00"/>
Datacenter/NOC	<input type="text"/>
Maximum No. of Accounts	<input type="text" value="200"/>
Server Status Address	<input type="text"/>
	To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. <a href="https://www.example.com/status/">https://www.example.com/status/</a>
Enable/Disable	<input type="checkbox"/> Check to disable this server

**Attention: Important Information**

The **hostname** field represents the actual domain of the server running Docker and must match the **server\_domain** parameter in the **n8n workflow**. If they do not match, communication will not function correctly. Additionally, this domain must be configured so that all its subdomains resolve to the IP address of the server running Docker.

The screenshot shows the 'Parameters' configuration page in n8n. At the top, there is a 'Test step' button. Below it, there are tabs for 'Parameters', 'Settings', and 'Docs'. The 'Mode' is set to 'Manual Mapping'. Under 'Fields to Set', there are two parameter entries:

- server\_domain**: Type 'String', value 'd01-test.uuq.pl' (underlined in red).
- clients\_dir**: Type 'String', value '/opt/docker/clients'.

In the **Server Details** section, select the "**PUQ Docker MinIO**" module and enter the correct **username** and **password** for the **API endpoint** in the n8n workflow.

Additionally, in the **Access Hash** field, insert the **URL of the API entry point** for the n8n workflow.

## Server Details

Module	<input type="text" value="PUQ Docker MinIO"/> <input type="button" value="Test Connection"/>
	✓ Connection successful. Some values have been auto-filled.
Username	<input type="text" value="minio"/>
Password	<input type="password" value="...."/>
Access Hash	<input type="text" value="https://n8n.puqcloud.com/webhook/docker-minio"/>
Secure	<input checked="" type="checkbox"/> Check to use SSL Mode for Connections

API Listen for test event

Parameters Settings Docs

Webhook URLs

Test URL Production URL

POST `https://n8n.puqcloud.com/webhook/docker-minio`

HTTP Methods

POST

Path

docker-minio

Authentication

Basic Auth

Credential for Basic Auth

Incom API User

Respond

Using 'Respond to Webhook' Node

Insert a 'Respond to Webhook' node to control when and how you respond. [More details](#)

Options

No properties

Add option

Revision #2

Created 14 March 2025 17:54:10 by Ruslan

Updated 21 March 2025 14:22:14 by Yuliia Noha