

Add server

Docker n8n module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#) | [n8n](#)

Add a new server to the system WHMCS.

System Settings->Servers->Add New Server

- Enter the correct **Name** and **Hostname**

Name	<input type="text" value="d01-test.uuq.pl"/>
Hostname	<input type="text" value="d01-test.uuq.pl"/>
IP Address	<input type="text"/>
Assigned IP Addresses (One per line)	<input type="text"/>
Monthly Cost	<input type="text" value="0.00"/>
Datacenter/NOC	<input type="text"/>
Maximum No. of Accounts	<input type="text" value="200"/>
Server Status Address	<input type="text"/> To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. https://www.example.com/status/
Enable/Disable	<input type="checkbox"/> Check to disable this server

Attention: Important Information

The **hostname** field represents the actual domain of the server running Docker and must match the **server_domain** parameter in the **n8n workflow**. If they do not match, communication will not function correctly. Additionally, this domain must be configured so that all its subdomains resolve to the IP address of the server running Docker.

The screenshot shows a configuration interface for parameters. At the top, there is a 'Test step' button. Below it, there are tabs for 'Parameters', 'Settings', and 'Docs'. The 'Parameters' tab is active. Under the 'Mode' section, a dropdown menu is set to 'Manual Mapping'. The 'Fields to Set' section contains two parameter configurations. The first is 'server_domain', which is a String type and has the value 'd01-test.uuq.pl' entered. The second is 'clients_dir', which is also a String type and has the value '/opt/docker/clients' entered.

In the **Server Details** section, select the "**PUQ Docker n8n**" module and enter the correct **username** and **password** for the **API endpoint** in the n8n workflow.

Additionally, in the **Access Hash** field, insert the **URL of the API entry point** for the n8n workflow.

Server Details

Module	PUQ Docker n8n 	<input type="button" value="Test Connection"/>
	✓ Connection successful. Some values have been auto-filled.	
Username	<input type="text" value="test"/>	
Password	<input type="password" value="...."/>	
Access Hash	<input type="text" value="https://n8n.puqcloud.com/webhook/docker-n8n"/>	
Secure	<input type="checkbox"/> Check to use SSL Mode for Connections	

API Listen for test event

Parameters Settings Docs

Webhook URLs

Test URL **Production URL**

POST `https://n8n.puqcloud.com/webhook/docker-n8n`

HTTP Methods

POST

Path

docker-n8n

Authentication

Basic Auth

Credential for Basic Auth

Incom API User

Respond

Using 'Respond to Webhook' Node

Insert a 'Respond to Webhook' node to control when and how you respond. [More details](#)

Options

No properties

Add option

Revision #4

Created 5 March 2025 04:14:47 by Ruslan

Updated 21 March 2025 13:39:48 by Yuliia Noha