

Add server

Docker NextCloud module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#) | [n8n](#)

Add a new server to the WHMCS system.

System Settings->Servers->Add New Server

- Enter the correct **Name** and **Hostname** for your server.

Name	<input type="text" value="d01-test.uuq.pl"/>
Hostname	<input type="text" value="d01-test.uuq.pl"/>
IP Address	<input type="text"/>
Assigned IP Addresses (One per line)	<input type="text"/>
Monthly Cost	<input type="text" value="0.00"/>
Datacenter/NOC	<input type="text"/>
Maximum No. of Accounts	<input type="text" value="200"/>
Server Status Address	<input type="text"/> To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. https://www.example.com/status/
Enable/Disable	<input type="checkbox"/> Check to disable this server

****Attention: Important Information**** The ****hostname**** field must precisely match the

domain configured as `server_domain` in the `n8n workflow`. Misalignment between these parameters will disrupt the communication between WHMCS and Docker. Furthermore, ensure this domain is configured so that all subdomains point correctly to the Docker server's IP address.

The screenshot shows a configuration window titled "Parameters". At the top right, there is a red button labeled "Test step". Below the title, there are tabs for "Parameters" (selected), "Settings", and "Docs". The "Mode" is set to "Manual Mapping". Under the "Fields to Set" section, there are two parameter entries:

- Parameter: `server_domain`, Type: `String`, Value: `d01-test.uuq.pl` (underlined in red).
- Parameter: `clients_dir`, Type: `String`, Value: `/opt/docker/clients`.

In the **Server Details** section, choose the module **"PUQ Docker NextCloud"**. Enter the accurate **username** and **password** as configured for the **API endpoint** in the `n8n workflow`.

Additionally, input the `URL of the API entry point` from the `n8n workflow` into the `Access Hash` field.

Server Details

Module	PUQ Docker NextCloud <input type="button" value="Test Connection"/>
	✓ Connection successful. Some values have been auto-filled.
Username	nextcloud
Password	●●●●●●●●●●●●●● <input type="button" value="👁"/>
Access Hash	https://n8n.puqcloud.com/webhook/docker-nextcloud
Secure	<input checked="" type="checkbox"/> Check to use SSL Mode for Connections

Webhook URLs

Test URL

Production URL

POST

<https://n8n.puqcloud.com/webhook-test/docker-nextcloud>

HTTP Methods

POST ×

Path

docker-nextcloud

Authentication

Basic Auth

Credential for Basic Auth

nextcloud ✎

Respond

Using 'Respond to Webhook' Node

Insert a 'Respond to Webhook' node to control when and how you respond. [More details](#)

Options

No properties

Add option

Revision #2

Created 27 February 2026 07:20:41 by Dmytro Kravchenko

Updated 27 February 2026 07:22:25 by Dmytro Kravchenko