

Installation and configuration guide

- [WHMCS setup\(install/update\)](#)
- [Setup guide: Emby setup](#)
- [Setup guide: WHMCS setup](#)
- [Add server \(Emby server\)](#)
- [Product Configuration](#)
- [Add new library/item in Emby](#)
- [Getting Access Hash \(API key\)](#)

WHMCS

setup(install/update)

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

Module is coded ionCube v13

Supported php version:

- php 7.4 WHMCS 8.11.0 -
- php 8.1 WHMCS 8.11.0 +
- php 8.2 WHMCS 8.11.0 +

To install and update a module, you must perform one and the same action.

1. Download the latest version of the module.

PHP 8.2

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/php82/PUQ_WHMCS-Emby-latest.zip
```

PHP 8.1

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/php81/PUQ_WHMCS-Emby-latest.zip
```

PHP 7.4

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/php74/PUQ_WHMCS-Emby-latest.zip
```

All versions are available via link:

http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/

2. Unzip the archive with the module.

```
unzip PUQ_WHMCS-Emby-latest.zip
```

3. Copy and Replace "puqEmby" to "WHMCS_WEB_DIR/modules/servers/"

Setup guide: Emby setup

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

1. Install Emby on your server

To simplify deployment and help automate this for as many users as possible, we provide a BASH script to handle repo installation as well as installing Emby. All you need to do is run this command on your system

```
wget https://github.com/MediaBrowser/Emby.Releases/releases/download/4.7.14.0/emby-server-deb_4.7.14.0_amd64.deb
```

```
dpkg -i emby-server-deb_4.7.14.0_amd64.deb
```

2. SSL certificate generation:

```
sudo apt install nginx certbot python3-certbot-nginx
```

```
sudo certbot --nginx --agree-tos --redirect --hsts --staple-ocsp --email YOUR_EMAIL -d DOMAIN_NAME
```

```
echo "0 0 * * * root certbot renew --quiet --no-self-upgrade --post-hook 'systemctl reload nginx'" | sudo tee -a /etc/cron.d/renew_certbot
```

3. Configure nginx from a subdomain

Create a file named nginx.conf.

```
cd /etc/nginx/conf.d/  
nano nginx.conf
```

Then, insert the following text, replacing **DOMAIN_NAME** with your domain.

```
# Uncomment the commented sections after you have acquired a SSL Certificate
server {
    listen 80;
    #listen [::]:80;
    server_name DOMAIN_NAME;

    # Uncomment to redirect HTTP to HTTPS
    return 302 https://$host$request_uri;
}

server {
    listen 443 ssl http2;
    #listen [::]:443 ssl http2;
    server_name DOMAIN_NAME;

    ## The default `client_max_body_size` is 1M, this might not be enough for some
posters, etc.
    client_max_body_size 20M;

    # use a variable to store the upstream proxy
    # in this example we are using a hostname which is resolved via DNS
    # (if you aren't using DNS remove the resolver line and change the variable to point
to an IP address e.g `set $emby 127.0.0.1`)
    set $emby 127.0.0.1;
    resolver 127.0.0.1 valid=30;

    ssl_certificate /etc/letsencrypt/live/DOMAIN_NAME/fullchain.pem;
    ssl_certificate_key /etc/letsencrypt/live/DOMAIN_NAME/privkey.pem;
    include /etc/letsencrypt/options-ssl-nginx.conf;
    ssl_dhparam /etc/letsencrypt/ssl-dhparams.pem;
    add_header Strict-Transport-Security "max-age=31536000" always;
    ssl_trusted_certificate /etc/letsencrypt/live/DOMAIN_NAME/chain.pem;
    ssl_stapling on;
    ssl_stapling_verify on;

    # Security / XSS Mitigation Headers
    # NOTE: X-Frame-Options may cause issues with the webOS app
    add_header X-Frame-Options "SAMEORIGIN";
```

```
add_header X-XSS-Protection "0"; # Do NOT enable. This is obsolete/dangerous
add_header X-Content-Type-Options "nosniff";

# COOP/COEP. Disable if you use external plugins/images/assets
add_header Cross-Origin-Opener-Policy "same-origin" always;
add_header Cross-Origin-Embedder-Policy "require-corp" always;
add_header Cross-Origin-Resource-Policy "same-origin" always;

# Permissions policy. May cause issues on some clients
add_header Permissions-Policy "accelerometer=(), ambient-light-sensor=(), battery=(),
bluetooth=(), camera=(), clipboard-read=(), display-capture=(), document-domain=(), encrypted-
media=(), gamepad=(), geolocation=(), gyroscope=(), hid=(), idle-detection=(), interest-
cohort=(), keyboard-map=(), local-fonts=(), magnetometer=(), microphone=(), payment=(),
publickey-credentials-get=(), serial=(), sync-xhr=(), usb=(), xr-spatial-tracking=()"
always;

# Tell browsers to use per-origin process isolation
add_header Origin-Agent-Cluster "?1" always;

# Content Security Policy
# See: https://developer.mozilla.org/en-US/docs/Web/HTTP/CSP
# Enforces https content and restricts JS/CSS to origin
# External Javascript (such as cast_sender.js for Chromecast) must be
whitelisted.
# NOTE: The default CSP headers may cause issues with the webOS app
#add_header Content-Security-Policy "default-src https: data: blob:
http://image.tmbd.org; style-src 'self' 'unsafe-inline'; script-src 'self' 'unsafe-inline'
https://www.gstatic.com https://www.youtube.com blob:; worker-src 'self' blob:; connect-src
'self'; object-src 'none'; frame-ancestors 'self'";

location = / {
    return 302 http://$host/web/;
    #return 302 https://$host/web/;
}

location / {
    # Proxy main Emby traffic
    proxy_pass http://$emby:8096;
    proxy_set_header Host $host;
```

```

        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_set_header X-Forwarded-Protocol $scheme;
        proxy_set_header X-Forwarded-Host $http_host;

        # Disable buffering when the nginx proxy gets very resource heavy upon
streaming
        proxy_buffering off;
    }

    # location block for /web - This is purely for aesthetics so /web/#!/ works instead
of having to go to /web/index.html/#!/
    location = /web/ {
        # Proxy main Emby traffic
        proxy_pass http://$emby:8096/web/index.html;
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_set_header X-Forwarded-Protocol $scheme;
        proxy_set_header X-Forwarded-Host $http_host;
    }

    location /socket {
        # Proxy Emby Websockets traffic
        proxy_pass http://$emby:8096;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "upgrade";
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_set_header X-Forwarded-Protocol $scheme;
        proxy_set_header X-Forwarded-Host $http_host;
    }
}

```

Restarting nginx

```
sudo service nginx restart
```

Setup guide: WHMCS setup

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

1. Download the latest version of the module.

PHP 8.1

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/PUQ_WHMCS-Emby-latest.zip
```

PHP 7.4

```
wget http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/php74/PUQ_WHMCS-Emby-latest.zip
```

All versions are available via link:

http://download.puqcloud.com/WHMCS/servers/PUQ_WHMCS-Emby/

2. Unzip the archive with the module.

```
unzip PUQ_WHMCS-Emby-latest.zip
```

3. Copy "puqEmby" to "WHMCS_WEB_DIR/modules/servers/"

4. Create new server Emby in WHMCS (System Settings->Products/Services->Servers)

```
System Settings->Servers->Add New Server
```

- Enter the correct **Name** and **Hostname**

Edit Server

Name	en[REDACTED].pl
Hostname	en[REDACTED].pl
IP Address	
Assigned IP Addresses (One per line)	
Monthly Cost	0.00
Datacenter/NOC	
Maximum No. of Accounts	200
Server Status Address	To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. https://www.example.com/status/
Enable/Disable	<input type="checkbox"/> Check to disable this server

- In the **Server Details** section, select the **"PUQ Emby"** module and enter the correct **username**, **password** and **access hash (API key)** for the **Emby web interface**.
- To check, click the **"Test connection"** button

Module	PUQ Emby	<input type="button" value="Test Connection"/>	✓ Connection successful. Some values have been auto-filled.
Username	admin		
Password		
Access Hash	4[REDACTED]3		
Secure	<input checked="" type="checkbox"/> Check to use SSL Mode for Connections		
Port	443	<input type="checkbox"/> Override with Custom Port	

5. Create a new Products/Services

System Settings->Products/Services->Create a New Product

In the **Module settings** section, select the **"PUQ Emby"** module

<p>Module Name: <input type="text" value="PUQ Emby"/></p> <p>Server Group: <input type="text" value="emby-test.uuq.pl"/></p>	
<p>License key: <input type="text" value="UNILKV-ZCNZCZ-FPTQPZ-ASFG9K-OELVAA"/> <small>success: 2026-04-15T11:58:03+02:00</small></p>	<p>Streaming bitrate limit: <input type="text" value="30"/> <small>Mbps. Please provide number from 1 to 60</small></p> <p>Remote control: <input checked="" type="checkbox"/> Remote control of shared devices (DLNA devices are considered shared until a user begins controlling them)</p> <p>Media downloads: <input type="checkbox"/> Users can download media and store it on their devices. This is not the same as a sync feature. Book libraries require this enabled to function properly.</p> <p>Subtitle Downloading: <input type="checkbox"/> Allow subtitle downloading</p> <p>Camera upload: <input type="checkbox"/> If allowed, and if enabled in Emby mobile apps, users can automatically upload photos and videos taken from their camera to this Emby Server</p> <p>Media conversion: <input type="checkbox"/> Grant or deny access to the convert media feature.</p> <p>Social media sharing: <input type="checkbox"/> Only web pages containing media information are shared. Media files are never shared publicly. Shares are time-limited and will expire after 30 days.</p> <p>User Preference Access: <input type="checkbox"/> Allow this user to change their password and profile image</p> <p>Username prefix: <input type="text" value="em-"/> <small>Will be attached to the beginning of username. Only small letters and numbers and symbol "-".</small></p> <p>Username suffix: <input type="text" value="-by"/> <small>Will be appended to the end of username. Only small letters and numbers and symbol "-".</small></p> <p>Allow Live TV access: <input checked="" type="checkbox"/></p> <p>Allow Live TV recording management: <input checked="" type="checkbox"/></p> <p>Force transcoding of remote media sources such as Live TV: <input type="checkbox"/></p>
<p>Libraries Configuration</p> <p>Use All Libraries: <input checked="" type="checkbox"/> select all libraries together</p> <div style="border: 1px solid #ccc; height: 30px; width: 100%;"></div> <p>Write down the libraries you want to make available to customers of this product. (IMPORTANT! Start a new line for each new library) Example: "Movies Beginner's Programming Course Comedy"</p> <p>IMPORTANT! If you have a folder named ".", please enter it not as the first one or rename it. If you don't want any folder to be accessible, type "-".</p>	<p>User Configuration</p>
<p>Allow playback</p> <p>media: <input checked="" type="checkbox"/></p> <p>audio that requires transcoding: <input checked="" type="checkbox"/></p> <p>video that requires transcoding: <input type="checkbox"/></p> <p>video that requires conversion without re-encoding: <input type="checkbox"/></p>	<p>Feature access</p>
<p>Links</p> <p>Instruction: <input type="text" value="https://doc.puq.info/books/emby-whmcs-n"/> <small>A link to the instruction will be reflected in the client area.</small></p>	<p>Client Area</p> <p>Show Password: <input type="text" value="Show button"/> <small>Show service password in the client area</small></p> <p>Password Generation: <input type="text" value="5:1234567890ABDab-d*0L"/> <small>Set the password length and the allowed letters/numbers/symbols for the password. Format: "8:234abcdABCD", where 8 is the password length, and everything after the colon represents the allowed characters.</small></p> <p>Username Format: <input type="text" value="Username generated by custom user"/> <small>{user_id}-{random_digit_5}-{random_letter_{random_letter_x}} {user_id}, {service_id}, {random_digit_x}, {random_letter_x}</small></p> <p>Custom Username: <input type="text" value="Unix time: {unixtime} Year: {year}, Month: {month}, Day: {day}, Hour: {hour}, Minute: {minute}, Second: {second}"/></p>
<p style="text-align: right;">Switch to Advanced Mode</p>	
<p><input type="radio"/> Automatically setup the product as soon as an order is placed</p> <p><input checked="" type="radio"/> Automatically setup the product as soon as the first payment is received</p> <p><input type="radio"/> Automatically setup the product when you manually accept a pending order</p> <p><input type="radio"/> Do not automatically setup this product</p>	

- **License key:** A pre-purchased license key for the "PUQ Emby" module. For the module to work correctly, the key must be active

Libraries:

- **Use All Libraries:** Choosing all of libraries from your Jellyfin server
- **Libraries:** The libraries you want to make available to customers of this product.
(IMPORTANT! Start a new line for each new library)

Example:

"Movies

Beginner`s Programming Course

Comedy"

IMPORTANT!

If you have a folder named "-", please enter it not as the first one or rename it.

If you don't want any folder to be accessible, type "-".

User Configuration:

- **Streaming bitrate limit:** An optional per-stream bitrate limit for all out of network devices. This is useful to prevent devices from requesting a higher bitrate than your internet connection can handle. This may result in increased CPU load on your server in order to transcode videos on the fly to a lower bitrate.
- **Remote control:** Remote control of shared devices (DLNA devices are considered shared until a user begins controlling them)
- **Media downloads:** Users can download media and store it on their devices. This is not the same as a sync feature. Book libraries require this enabled to function properly.
- **Subtitle Downloading:** Allow subtitle downloading
- **Camera upload:** If allowed, and if enabled in Emby mobile apps, users can automatically upload photos and videos taken from their camera to this Emby Server
- **Media conversion:** Grant or deny access to the convert media feature.
- **Social media sharing:** Only web pages containing media information are shared. Media files are never shared publicly. Shares are time-limited and will expire after 30 days.
- **User Preference Access:** Allow this user to change their password and profile image
- **Username prefix/Username suffix:** Necessary in order to generate a username for the service, in the format: **prefix<client_id>-<service_id>suffix**

Allow playback (Restricting access to transcoding may cause playback failures in clients due to unsupported media formats)

- **media**
- **audio that requires transcoding**
- **video that requires transcoding**
- **video that requires conversion without re-encoding**

Feature access:

- **Allow Live TV access**
- **Allow Live TV recording management**
- **Force transcoding of remote media sources such as Live TV**

Links

- **Link to instruction:** Link to the instruction, if filled out, it will be reflected in the client area

Client Area

- **Show Password** - Show the service password in the client area.
- **Password Generation** - Set the password length and the allowed letters/numbers/symbols for the password.
Format: "8: 234abcdABCD", where 8 is the password length, and everything after the colon represents the allowed characters.
- **Username Format** - Define the format for username generation:
 - **Standard** - prefix-client_id-service_id-suffix
 - **Custom** - username generated by a custom rule
- **Custom Username** - Set a rule for generating a custom username.

Add server (Emby server)

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

Add a new server to the system WHMCS.

System Settings->Servers->Add New Server

- Enter the correct **Name** and **Hostname**

Edit Server

Name	<input type="text" value="em[REDACTED].pl"/>
Hostname	<input type="text" value="em[REDACTED].pl"/>
IP Address	<input type="text"/>
Assigned IP Addresses (One per line)	<input type="text"/>
Monthly Cost	<input type="text" value="0.00"/>
Datacenter/NOC	<input type="text"/>
Maximum No. of Accounts	<input type="text" value="200"/>
Server Status Address	<input type="text"/> <small>To display this server on the server status page, enter the full path to the server status folder (required to be uploaded to each server you want to monitor) - eg. https://www.example.com/status/</small>
Enable/Disable	<input type="checkbox"/> Check to disable this server

- In the **Server Details** section, select the "**PUQ Emby**" module and enter the correct **username**, **password** and **access hash (API key)** for the **Emby web interface**
- To check, click the "**Test connection**" button

Module PUQ Emby Test Connection ✓ Connection successful. Some values have been auto-filled.

Username

Password

Access Hash

Secure Check to use SSL Mode for Connections

Port Override with Custom Port

Save Changes

Cancel Changes

Product Configuration

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

Create a new Products/Services

System Settings->Products/Services->Create a New Product

In the **Module settings** section, select the "**PUQ Emby**" module

Details
Pricing
Module Settings
Custom Fields
Configurable Options
Upgrades
Free Domain
Cross-sells
Other
Links

Module Name:

Server Group:

License key:
success: 2026-04-15T11:58:03+02:00

Libraries Configuration

Use All Libraries: select all libraries together

Write down the libraries you want to make available to customers of this product.
(IMPORTANT! Start a new line for each new library)
 Example:
 "Movies
 Beginner's Programming Course
 Comedy"

IMPORTANT!
 If you have a folder named ".", please enter it not as the first one or rename it.
 If you don't want any folder to be accessible, type ".".

User Configuration

Streaming bitrate limit:
Mbps. Please provide number from 1 to 60

Remote control: Remote control of shared devices (DLNA devices are considered shared until a user begins controlling them)

Media downloads: Users can download media and store it on their devices. This is not the same as a sync feature. Book libraries require this enabled to function properly.

Subtitle Downloading: Allow subtitle downloading

Camera upload: If allowed, and if enabled in Emby mobile apps, users can automatically upload photos and videos taken from their camera to this Emby Server

Media conversion: Grant or deny access to the convert media feature.

Social media sharing: Only web pages containing media information are shared. Media files are never shared publicly. Shares are time-limited and will expire after 30 days.

User Preference Access: Allow this user to change their password and profile image

Username prefix:
Will be attached to the beginning of username. Only small letters and numbers and symbol "-".

Username suffix:
Will be appended to the end of username. Only small letters and numbers and symbol "-".

Allow playback

media:

audio that requires transcoding:

video that requires transcoding:

video that requires conversion without re-encoding:

Feature access

Allow Live TV access:

Allow Live TV recording management:

Force transcoding of remote media sources such as Live TV:

Links

Instruction:
A link to the instruction will be reflected in the client area.

Client Area

Show Password:
Show service password in the client area

5:1234567890ABDab-d*0L

Set the password length and the allowed letters/numbers/symbols for the password.
Format: "8:234abcdABCD", where 8 is the password length, and everything after the colon represents the allowed characters.

Username Format:
{user_id}-{random_digit_5}-{random_letter_{random_letter_x}}

Custom Username:

[Switch to Advanced Mode](#)

Automatically setup the product as soon as an order is placed

Automatically setup the product as soon as the first payment is received

Automatically setup the product when you manually accept a pending order

Do not automatically setup this product

- **License key:** A pre-purchased license key for the "PUQ Emby" module. For the module to work correctly, the key must be active

Libraries:

- **Use All Libraries:** Choosing all of libraries from your Jellyfin server
- **Libraries:** The libraries you want to make available to customers of this product.
(IMPORTANT! Start a new line for each new library)

Example:

"Movies

Beginner`s Programming Course

Comedy"

IMPORTANT!

If you have a folder named "-", please enter it not as the first one or rename it.

If you want to select all folders together, simply leave the field EMPTY.

If you don't want any folder to be accessible, type "-".

User Configuration:

- **Streaming bitrate limit:** An optional per-stream bitrate limit for all out of network devices. This is useful to prevent devices from requesting a higher bitrate than your internet connection can handle. This may result in increased CPU load on your server in order to transcode videos on the fly to a lower bitrate.
- **Remote control:** Remote control of shared devices (DLNA devices are considered shared until a user begins controlling them)
- **Media downloads:** Users can download media and store it on their devices. This is not the same as a sync feature. Book libraries require this enabled to function properly.
- **Subtitle Downloading:** Allow subtitle downloading
- **Camera upload:** If allowed, and if enabled in Emby mobile apps, users can automatically upload photos and videos taken from their camera to this Emby Server
- **Media conversion:** Grant or deny access to the convert media feature.
- **Social media sharing:** Only web pages containing media information are shared. Media files are never shared publicly. Shares are time-limited and will expire after 30 days.
- **User Preference Access:** Allow this user to change their password and profile image
- **Username prefix/Username suffix:** Necessary in order to generate a username for the service, in the format: **prefix<client_id>-<service_id>suffix**

Allow playback (Restricting access to transcoding may cause playback failures in clients due to unsupported media formats)

- **media**
- **audio that requires transcoding**
- **video that requires transcoding**
- **video that requires conversion without re-encoding**

Feature access:

- **Allow Live TV access**
- **Allow Live TV recording management**
- **Force transcoding of remote media sources such as Live TV**

Links

- **Link to instruction:** Link to the instruction, if filled out, it will be reflected in the client

area

Client Area

- **Show Password** - Show the service password in the client area.
- **Password Generation** - Set the password length and the allowed letters/numbers/symbols for the password.
Format: `"8: 234abcdABCD"`, where `8` is the password length, and everything after the colon represents the allowed characters.
- **Username Format** - Define the format for username generation:
 - **Standard** - prefix-client_id-service_id-suffix
 - **Custom** - username generated by a custom rule
- **Custom Username** - Set a rule for generating a custom username.

Add new library/item in Emby

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

New library:

To create a new library, you should to **create a folder** in your Emby server.

First, navigate to the root of your project "/" and enter the following commands:


```
cd mnt
```

```
mkdir LIBRARY_NAME
```





LIBRARY_NAME - The name of the new library.

After creating a folder, let's create a library in Emby:

Add a new library:



← Library ?

Get Emby Premiere    

Libraries Advanced

0 Libraries + New Library Scan Library Files

Assign the appropriate folder to this library:

Show advanced settings

Content type:

Movies

Review the [Emby movie naming guide](#).

Display name:

Movies

Folders



Library Settings

Preferred metadata download language:

Country:

Preferred image download language:

Okay

← Select Path

Network paths can be entered manually in the event the Network button fails to locate your devices. For example, `\\server` or `\\192.168.1.101`.

For Linux on Arch Linux, CentOS, Debian, Fedora, OpenSuse, or Ubuntu, you must grant the Emby system user at least read access to your storage locations.

Folder:



(Optional) Shared network folder:

If this folder is shared on your network, supplying the network share path can allow Emby apps on other devices to access media files directly.

Okay

New item:

To download a new item, navigate to the root of your project "/" and enter the following commands:

```
cd mnt/LIBRARY_NAME
```



```
wget DOWNLOAD_ITEM_URL
```

LIBRARY_NAME - The name of the library.

DOWNLOAD_ITEM_URL - The download URL of the item you want to upload to the server.

After all

Scan all libraries by clicking on the "Scan All Libraries" button, or by clicking on the three dots and selecting "Scan Library Files".



Getting Access Hash (API key)

Emby module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

Dashboard -> API Keys

Create a new API Key

The screenshot shows the Emby web interface for managing API keys. On the left is a sidebar menu with categories: Network, Transcoding, Database, Conversions, Cinema Intros, Open Subtitles, Webhooks, Devices (with a dropdown arrow), and Advanced (with a dropdown arrow). Under 'Devices', there are links for Devices, Downloads, Camera Upload, and DLNA. Under 'Advanced', there are links for Logs, Notifications, Plugins, Scheduled Tasks, API Keys (highlighted in green), and Metadata Manager. The main content area is titled 'API Keys' and shows '0 items' with a '+ New API Key' button. Below this, it says 'No items found.' In the top right corner, there is a 'Get Emby Premiere' button and icons for search, user profile, and settings.

Whrite an App Name

← New API Key

App name


Example: Sickbeard, NzbDrone

Okay

Now you can getting an API key

← API Keys

Get Emby Premiere



1 Item + New API Key

4 [redacted] 3 - WHMCS module
09/11/2023, 11:58:00

