Setup guide: Emby setup

Emby module **WHMCS**

Order now | Download | FAQ

1. Install Emby on your server

To simplify deployment and help automate this for as many users as possible, we provide a BASH script to handle repo installation as well as installing Emby. All you need to do is run this command on your system

```
wget https://github.com/MediaBrowser/Emby.Releases/releases/download/4.7.14.0/emby-server-deb_4.7.14.0_amd64.deb
```

```
dpkg -i emby-server-deb_4.7.14.0_amd64.deb
```

2. SSL certificate generation:

```
sudo apt install nginx certbot python3-certbot-nginx
```

```
sudo certbot --nginx --agree-tos --redirect --hsts --staple-ocsp --email YOUR_EMAIL -d DOMAIN_NAME
```

```
echo "0 0 * * *  root  certbot renew --quiet --no-self-upgrade --post-hook 'systemctl reload nginx'" | sudo tee -a /etc/cron.d/renew_certbot
```

3. Configure nginx from a subdomain

Create a file named nginx.conf.

```
cd /etc/nginx/conf.d/
nano nginx.conf
```

Then, insert the following text, replacing DOMAIN_NAME with your domain.

```
# Uncomment the commented sections after you have acquired a SSL Certificate
server {
        listen 80;
        #listen [::]:80;
        server_name DOMAIN_NAME;

        # Uncomment to redirect HTTP to HTTPS
        return 302 https://$host$request_uri;
}

server {
        listen 443 ssl http2;
        #listen [::]:443 ssl http2;
        server_name DOMAIN_NAME;

        ## The default `client_max_body_size` is 1M, this might not be enough for some
posters, etc.
        client_max_body_size 20M;

        # use a variable to store the upstream proxy
        # in this example we are using a hostname which is resolved via DNS
        # (if you aren't using DNS remove the resolver line and change the variable to point
to an IP address e.g `set $emby 127.0.0.1`)
        set $emby 127.0.0.1;
        resolver 127.0.0.1 valid=30;

        ssl_certificate /etc/letsencrypt/live/DOMAIN_NAME/fullchain.pem;
        ssl_certificate_key /etc/letsencrypt/live/DOMAIN_NAME/privkey.pem;
        include /etc/letsencrypt/options-ssl-nginx.conf;
        ssl_dhparam /etc/letsencrypt/ssl-dhparams.pem;
        add_header Strict-Transport-Security "max-age=31536000" always;
        ssl_trusted_certificate /etc/letsencrypt/live/DOMAIN_NAME/chain.pem;
        ssl_stapling on;
        ssl_stapling_verify on;
```

```
        # Security / XSS Mitigation Headers
        # NOTE: X-Frame-Options may cause issues with the webOS app
        add_header X-Frame-Options "SAMEORIGIN";
        add_header X-XSS-Protection "0"; # Do NOT enable. This is obsolete/dangerous
        add_header X-Content-Type-Options "nosniff";

        # COOP/COEP. Disable if you use external plugins/images/assets
        add_header Cross-Origin-Opener-Policy "same-origin" always;
        add_header Cross-Origin-Embedder-Policy "require-corp" always;
        add_header Cross-Origin-Resource-Policy "same-origin" always;

        # Permissions policy. May cause issues on some clients
        add_header Permissions-Policy "accelerometer=(), ambient-light-sensor=(), battery=(),
bluetooth=(), camera=(), clipboard-read=(), display-capture=(), document-domain=(), encrypted-
media=(), gamepad=(), geolocation=(), gyroscope=(), hid=(), idle-detection=(), interest-
cohort=(), keyboard-map=(), local-fonts=(), magnetometer=(), microphone=(), payment=(),
publickey-credentials-get=(), serial=(), sync-xhr=(), usb=(), xr-spatial-tracking=()"
always;

        # Tell browsers to use per-origin process isolation
        add_header Origin-Agent-Cluster "?1" always;


        # Content Security Policy
        # See: https://developer.mozilla.org/en-US/docs/Web/HTTP/CSP
        # Enforces https content and restricts JS/CSS to origin
        # External Javascript (such as cast_sender.js for Chromecast) must be
whitelisted.
        # NOTE: The default CSP headers may cause issues with the webOS app
        #add_header Content-Security-Policy "default-src https: data: blob:
http://image.tmdb.org; style-src 'self' 'unsafe-inline'; script-src 'self' 'unsafe-inline'
https://www.gstatic.com https://www.youtube.com blob:; worker-src 'self' blob:; connect-src
'self'; object-src 'none'; frame-ancestors 'self'";

        location = / {
                return 302 http://$host/web/;
                #return 302 https://$host/web/;
        }

        location / {
```

```
                # Proxy main Emby traffic
                proxy_pass http://$emby:8096;
                proxy_set_header Host $host;
                proxy_set_header X-Real-IP $remote_addr;
                proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
                proxy_set_header X-Forwarded-Proto $scheme;
                proxy_set_header X-Forwarded-Protocol $scheme;
                proxy_set_header X-Forwarded-Host $http_host;

                # Disable buffering when the nginx proxy gets very resource heavy upon
streaming
                proxy_buffering off;
        }

        # location block for /web - This is purely for aesthetics so /web/#!/ works instead
of having to go to /web/index.html/#!/
        location = /web/ {
                # Proxy main Emby traffic
                proxy_pass http://$emby:8096/web/index.html;
                proxy_set_header Host $host;
                proxy_set_header X-Real-IP $remote_addr;
                proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
                proxy_set_header X-Forwarded-Proto $scheme;
                proxy_set_header X-Forwarded-Protocol $scheme;
                proxy_set_header X-Forwarded-Host $http_host;
        }

        location /socket {
                # Proxy Emby Websockets traffic
                proxy_pass http://$emby:8096;
                proxy_http_version 1.1;
                proxy_set_header Upgrade $http_upgrade;
                proxy_set_header Connection "upgrade";
                proxy_set_header Host $host;
                proxy_set_header X-Real-IP $remote_addr;
                proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
                proxy_set_header X-Forwarded-Proto $scheme;
                proxy_set_header X-Forwarded-Protocol $scheme;
                proxy_set_header X-Forwarded-Host $http_host;
        }
```

```
}
```

Restarting nginx

```
sudo service nginx restart
```

Revision #6
Created 8 November 2023 05:49:33 by Yuliia Noha
Updated 21 December 2023 06:08:16 by Yuliia Noha