

# Product Configuration

## MinIO S3 module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

### Add new product to WHMCS

System Settings->Products/Services->Create a New Product

In the **Module settings** section, select the "**PUQ MinIOS3**" module

Edit Product

Details Pricing **Module Settings** Custom Fields Configurable Options Upgrades Free Domain Cross-sells Other Links

Module Name: PUQ MinIO S3  
Server Group: None

License key: ANRLF6-...PMAHLH success: 2024-09-10T12:46:27+02:00	Unit: GigaByte Unit of measure in the product
Disk space size: 1 in unit	Notification disk limit email template: puqMinIOS3 Notification di
Notification, used disk space X %: 50	Username prefix: 333- Will be attached to the beginning of username. Only small letters and numbers and symbol "-"
Username postfix: -777 Will be appended to the end of username. Only small letters and numbers and symbol "-"	Group: USERS1
Raw Policy: { "Version": "2012-10-17", "Statement": { "Effect": "Allow", <USER_ID> - Macro to be replaced}}	Suspend exceeding disk limit email template: puqMinIOS3 service Suspe
Save usage history (days): 365 0 - all history	Link to instruction: https://doc.puq.info/books/minio-s3-whmcs-module A link to the instruction will be reflected in the client area.
Default Bucket: Create default bucket: Yes Once the user is created, a default bucket will be created. Default bucket postfix: Will be appended to the end of bucket name. Only small letters and numbers and symbol "-"	Client Area: Show Password: Show button Show service password in the client area

- **License key:** A pre-purchased license key for the "**PUQ MinIOS3**" module. For the module to work correctly, the key must be active
- **Unit:** Packet disk space units
- **Disk space size:** Disk size in this product
- **Notification disk limit email template:** Email template that will be sent when the disk quota is exceeded in %
- **Notification, used disk space X %:** Sets a percentage parameter, after exceeding this parameter a notification will be sent to the user

- **Username prefix/Username suffix:** Necessary in order to generate a username for the service, in the format: **prefix<client\_id>-<service\_id>suffix**
- **Group:** The group that will be assigned to the user on the server side of the **MinIO S3**
- **Raw Policy:** The policy that is assigned to the user during creation on the server

Example:

**In the given policy example. The user has the right to create buckets with a name starting with the username.**

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "admin: Heal",
        "admin: SetBucketTarget",
        "admin: TopLocksInfo",
        "admin: DataUsageInfo",
        "admin: GetBucketQuota",
        "admin: GetBucketTarget"
      ],
      "Resource": [
        "arn:aws:s3:: <USER_ID>*"
      ]
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3: *"
      ],
      "Resource": [
        "arn:aws:s3:: <USER_ID>*"
      ]
    }
  ]
}
```

- **Suspend exceeding disk limit email template:** The template of the letter that will be

sent to the client if his disk limit is 100% or less 100%

- **Save usage history (days):** The number of days it takes to save user disk usage statistics
- **Link to instruction:** Link to the instruction, if filled out, it will be reflected in the client area
- **Default Bucket:** Options to enable or disable the creation of a default bucket, and also set its prefix
- **Client Area:** Client zone settings, show or not show the password in the client zone, type how to show the password.

---

Revision #7

Created 9 August 2022 12:11:55 by Ruslan

Updated 21 December 2023 07:11:40 by Ruslan