

DNS Zones

PUQ Customization module **WHMCS**

[Order now](#) | [Download](#) | [FAQ](#)

Instructions: Configuring DNS Synchronization for Virtual Machines in puqProxmoxKVM

In order to enable DNS records synchronization for virtual machines managed by the puqProxmoxKVM module, you have the option to create DNS zones. A DNS zone is an object that is part of the API connection configuration to the DNS provider, allowing the puqProxmoxKVM module to synchronize DNS records.

How it Works:

1. When creating a new service, modifying an existing one, or when a client requests a change to their virtual machine's revDNS record, the module will attempt to find the corresponding DNS zone for synchronization.
 - Forward Zone: The domain and subdomain are taken from the service's Domain field, and the module matches them with the added zones. If there's a match, it performs actions to synchronize the A and AAAA records. The IPv4 address is taken from the Allocated IP field for the service, and for IPv6 synchronization, the first available IPv6 address for that service is used.
 - Reverse Zone: All IP addresses are converted into a DNS zone, which is then compared with the list of existing zones. When there's a match, the records are synchronized.

By synchronization, it means that the records will be removed from the remote server and then recreated. Except for service creation, where records are created without deletion. Also, when a service is deleted, the records will be deleted and not recreated.

After adding the zone, you can click the "Test Zone" button to verify the correctness of the added data and perform a test on the DNS provider using the API.

Supported DNS Providers:

cloudflare.com

- Required data for zone creation:
 - Zone Name
 - Zone ID
 - Account ID
 - API Token Before adding a zone, you must create the zone on the service and obtain all the necessary data with sufficient access rights.

Home

Module puqProxmoxKVM -

IP Pools

DNS Zones

Account Statement +

Admin Panel Unique +

Auto CC Management +

Blocking ticket for guests+

Cancel Fund Invoices +

Client Data Archive +

Client Grouping Rules +

Clients Only Access +

Credit Management +

Disabler of standard elements +

Fraud Check +

GDPR Tools +

Successfully!

Connection successfully

DNS Zones

Module puqProxmoxKVM i

Edit Zone (cloudflare.com)

Zone

polovyl.com

Forward zone: example.com

Reverse zone IPv4: 100.51.198.in-addr.arpa (IPv4 prefix: 198.51.100.0/24)

Reverse zone IPv6: d.c.b.a.d.c.b.a.d.c.b.a.8.b.d.0.1.0.0.2.ip6.arpa (IPv6 prefix: 2001:0db8:abcd:abcd:abcd:abcd:0000/112)

Cloudflare Zone ID

610488689b81

Cloudflare Account ID

63f3d02dab0ac

Cloudflare API Token

okxTLA-BE

Edit Zone

Test Zone

Delete Zone

HestiaCP Server

- Required data for zone creation:
 - Zone
 - Hestiacp server
 - Hestiacp admin user
 - Hestiacp admin password
 - User (The user who will be the holder of the DNS zones) When adding a zone, create it on the remote server and allow WHMCS access to the HestiaCP server via API.

Successfully!
Connection successfully

DNS Zones

Module puqProxmoxKVM i

Edit Zone (hestiacp)

Zone

polovyl.com

Forward zone: example.com

Reverse zone IPv4: 100.51.198.in-addr.arpa (IPv4 prefix: 198.51.100.0/24)

Reverse zone IPv6: d.c.b.a.d.c.b.a.d.c.b.a.8.b.d.0.1.0.0.2.ip6.arpa (IPv6 prefix: 2001:0db8:abcd:abcd:abcd:abcd:0000/112)

Hestiacp server

https://hestiacp-test.uuq.pl:8083/

Hestiacp server: https://example.com:8083/

Hestiacp admin user

admin

Server administrator username

Hestiacp admin password

2sCAfnb

Server administrator user password

User

proxmox-dns

The user who will be the holders of the DNS zones

Edit Zone

Test Zone

Delete Zone

Note:

- The synchronization will occur for all matching zones. If you add two identical zones on different DNS providers, synchronization will occur for both of these identical zones.
- Synchronization is not instantaneous but occurs at scheduled cron tasks and may take some time.
- If there are any connection errors or other issues during the synchronization process, they will be logged in the module's logs. Synchronization errors will not stop the service or disrupt automation processes.

DNS Zones

Module puqProxmoxKVM i

Add Zone (cloudflare.com)

Add Zone (HestiaCP)

ID	Zone	DNS provider type
#1	polovyl.com	cloudflare
#3	125.87.77.in-addr.arpa	cloudflare
#4	0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.f.f.1.1.a.2.ip6.arpa	cloudflare
#5	polovyl.com	hestiacp
#6	0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.f.f.1.1.a.2.ip6.arpa	hestiacp
#7	125.87.77.in-addr.arpa	hestiacp