

# Check online users

[Order now](#) | [Download](#) | [FAQ](#)

## Check online users WireGuard protocol

**Request Structure:** `https://<puqvpnpv>/api/v1/wireguard/online`

**Method:** `GET`

**Cookie:** `access_hash=<access_hash>`

### Example:

```
curl \
-b
"access_hash=def77a57825907131fca3ba92fc22970ffe7429fd8b49535e178f59542c42cf2be854e296941de9f"
\
-X GET https://dev.softkeel.com/api/v1/wireguard/online
```

### Response example:

```
{
  "error" : "",
  "msg" : [
    {
      "allowed_IPs" : "10.0.110.17",
      "b_download" : "10",
      "b_upload" : "10",
      "endpoint" : "79.184.218.180:47471",
      "latest_handshake" : "2022-12-12 13:02:01",
      "name" : "ruslan_telefon",
      "status" : "enable",
```

```
    "transfer_rx" : "3892",
    "transfer_tx" : "2972",
    "username" : "user_32",
    "wg_name" : "77_87_125_209"
  },
  {
    "allowed_IPs" : "10.0.110.12",
    "b_download" : "30",
    "b_upload" : "30",
    "endpoint" : "77.87.125.204:59558",
    "latest_handshake" : "2022-12-12 13:01:48",
    "name" : "test_mac",
    "status" : "enable",
    "transfer_rx" : "2244",
    "transfer_tx" : "3356",
    "username" : "test_mac",
    "wg_name" : "77_87_125_209"
  }
],
"status" : "success"
}
```

#### Errors:

-Not authorized

# Check online users IKEv2 protocol

**Request Structure:** `https://<puqvpnpv>/api/v1/ikev2/online`

**Method:** `GET`

**Cookie:** `access_hash=<access_hash>`

#### Example:

```
curl \
-b
"access_hash=def77a57825907131fca3ba92fc22970ffe7429fd8b49535e178f59542c42cf2be854e296941de9f"
```

```
\
-X GET https://dev.softkeel.com/api/v1/ikev2/online
```

### Response example:

```
{
  "error" : "",
  "msg" : [
    {
      "allowed_IPs" : "10.0.110.17",
      "b_download" : "10",
      "b_upload" : "10",
      "endpoint" : "79.184.218.180",
      "name" : "ruslan_telefon",
      "status" : "enable",
      "uptime" : " 11 seconds ago",
      "username" : "user_32",
      "wg_name" : "77_87_125_209"
    },
    {
      "allowed_IPs" : "10.0.110.12",
      "b_download" : "30",
      "b_upload" : "30",
      "endpoint" : "77.87.125.204",
      "name" : "test_mac",
      "status" : "enable",
      "uptime" : " 4 seconds ago",
      "username" : "test_mac",
      "wg_name" : "77_87_125_209"
    }
  ],
  "status" : "success"
}
```

### Errors:

```
-Not authorized
```

### Errors:

- Not authorized

---

# Drop user connection IKEv2 protocol

**Request Structure:** `https://<puqvpnpv>/api/v1/ikev2/online/<NAME>`

**Cookie:** `access_hash=<access_hash>`

**Method:** `DELETE`

## Example:

```
curl \
-b
"access_hash=def77a57825907131fca3ba92fc22970ffe7429fd8b49535e178f59542c42cf2be854e296941de9f"
\
-X DELETE https://dev.softkeel.com/api/v1/ikev2/online/ruslan_telefon
```

## Response example:

```
{
  "error" : "",
  "msg" : "success",
  "status" : "success"
}
```

## Errors:

- Not authorized

---

---

Revision #11

Created 12 December 2022 11:47:03 by Ruslan

Updated 16 October 2023 10:13:49 by Yuliia Noha