

Check online users

[Order now](#) | [Download](#) | [FAQ](#)

Check online users WireGuard protocol

Request Structure: `https://<puqvpnpv>/api/v1/wireguard/online`

Method: `GET`

Cookie: `access_hash=<access_hash>`

Example:

```
curl \
-b
"access_hash=def77a57825907131fca3ba92fc22970ffe7429fd8b49535e178f59542c42cf2be854e296941de9f"
\
-X GET https://dev.softkeel.com/api/v1/wireguard/online
```

Response example:

```
{
  "error" : "",
  "msg" : [
    {
      "allowed_IPs" : "10.0.110.17",
      "b_download" : "10",
      "b_upload" : "10",
      "endpoint" : "79.184.218.180:47471",
      "latest_handshake" : "2022-12-12 13:02:01",
      "name" : "ruslan_telefon",
      "status" : "enable",
```

```
    "transfer_rx" : "3892",
    "transfer_tx" : "2972",
    "username" : "user_32",
    "wg_name" : "77_87_125_209"
  },
  {
    "allowed_IPs" : "10.0.110.12",
    "b_download" : "30",
    "b_upload" : "30",
    "endpoint" : "77.87.125.204:59558",
    "latest_handshake" : "2022-12-12 13:01:48",
    "name" : "test_mac",
    "status" : "enable",
    "transfer_rx" : "2244",
    "transfer_tx" : "3356",
    "username" : "test_mac",
    "wg_name" : "77_87_125_209"
  }
],
"status" : "success"
}
```

Errors:

```
-Not authorized
```

Check online users IKEv2 protocol

Request Structure: `https://<puqvpnpv>/api/v1/ikev2/online`

Method: `GET`

Cookie: `access_hash=<access_hash>`

Example:

```
curl \
-b
"access_hash=def77a57825907131fca3ba92fc22970ffe7429fd8b49535e178f59542c42cf2be854e296941de9f"
```

```
\
-X GET https://dev.softkeel.com/api/v1/ikev2/online
```

Response example:

```
{
  "error" : "",
  "msg" : [
    {
      "allowed_IPs" : "10.0.110.17",
      "b_download" : "10",
      "b_upload" : "10",
      "endpoint" : "79.184.218.180",
      "name" : "ruslan_telefon",
      "status" : "enable",
      "uptime" : " 11 seconds ago",
      "username" : "user_32",
      "wg_name" : "77_87_125_209"
    },
    {
      "allowed_IPs" : "10.0.110.12",
      "b_download" : "30",
      "b_upload" : "30",
      "endpoint" : "77.87.125.204",
      "name" : "test_mac",
      "status" : "enable",
      "uptime" : " 4 seconds ago",
      "username" : "test_mac",
      "wg_name" : "77_87_125_209"
    }
  ],
  "status" : "success"
}
```

Errors:

```
-Not authorized
```

Errors:

-Not authorized

Drop user connection IKEv2 protocol

Request Structure: `https://<puqvpnpv>/api/v1/ikev2/online/<NAME>`

Cookie: `access_hash=<access_hash>`

Method: `DELETE`

Example:

```
curl \  
-b \  
"access_hash=def77a57825907131fca3ba92fc22970ffe7429fd8b49535e178f59542c42cf2be854e296941de9f" \  
\ \  
-X DELETE https://dev.softkeel.com/api/v1/ikev2/online/ruslan_telefon
```

Response example:

```
{  
  "error" : "",  
  "msg" : "success",  
  "status" : "success"  
}
```

Errors:

-Not authorized

Revision #11

Created 12 December 2022 04:47:03 by Ruslan

Updated 16 October 2023 03:13:49 by Yuliia Noha