

Enable IKEv2

[Order now](#) | [Download](#) | [FAQ](#)

It is worth remembering that the main VPN protocol in the panel is **WireGuard**, and the **IKEv2** protocol is an additional protocol. This means that before using **IKEv2**, you must configure the **WireGuard** protocol, and then enable **IKEv2** support on each **WireGuard** interface on which you want to use **IKEv2**.

For the inclusion of the **IKEv2** protocol, switch to the configuration of the **WireGuard** user interface

To enable the **IKEv2** protocol, switch to the desired **WireGuard** interface.

PUQVPNCP

? HELP ?

ruslan (79.184.3.204)

Logout

Dashboard

VPN servers

WireGuard

IKEv2

VPN accounts

Settings

About us

WireGuard

Create

Find By Name

Peers

IKEv2

Find By Interface

Find By Network

Internal Traffic Port

External IP

DNS

Peer Download

Peer Upload

Keepalive

1-4819	0	YES	wg7	10.0.6.1/24	YES	51827	77.87.125.209	8.8.8.8	1.1.1.1	3M	4M	5	Edit	Delete
1-4820	1	YES	wg8	10.0.7.1/24	YES	51828	77.87.125.200	8.8.8.8	1.1.1.1	3M	4M	0	Edit	Delete
77_87_125_209	12	YES	wg110	10.0.110.1/24	YES	51930	77.87.125.200	10.0.110.1	77.87.125.200	30M	30M	5	Edit	Delete
Default	34	YES	wg0	13.11.11.10/24	NO	51820	77.87.125.200	8.8.8.8	1.1.1.1	10M	5M	0	Edit	Delete

PUQVPNCP

Dashboard

VPN servers

VPN accounts

Settings

About us

WireGuard / Edit WireGuard

Save

Set Bandwidth

Name

77.87.125.209

Interface name

wg110

Private key

UAI3hlyFmkQpo+bX2WbfbF3lys3Vyyd

Public key

xbrwVHxNZ8UsjHQyyzFwmOEy1UC+

IP/MASK

10.0.110.1/24

Internal Traffic

ACCEPT

Port

51930

External IP

77.87.125.200

DNS 1

10.0.110.1

DNS 2

77.87.125.200

Peers configuration

Bandwidth download (in M) per peer

30

Bandwidth upload (in M) per peer

30

Persistent Keepalive

5

0 - disabled

IKEv2 Enabled

YES

Public key

xbrwVHxNZ8UsjHQyyzFwmOEy1UC+vvKQ0FG/cLoJh2w=

Port

51930

Firewall Nat

10.0.110.0/24 -> 0.0.0.0/0 SNAT to:77.87.125.200 Pkt:53 Bytes:3312

Firewall Filter

10.0.110.0/24 -> 10.0.110.0/24 ACCEPT Pkt:0 Bytes:0

Traffic Control

qdisc htb 1: root refcnt 2 r2q 10 default 0 direct_packets_stat 9 direct_qlen 1000
Sent 5200 bytes 18 pkt (dropped 0, overlimits 0 requeues 0)
backlog 0b 0p requeues 0

Name	Status	IP	Download Upload	Mangle	
dimon_pc	Enable	10.0.110.5	30M 30M	324	<div>Edit</div>
dimon_telefon	Enable	10.0.110.7	30M 30M	110	<div>Edit</div>
dino_pc	Enable	10.0.110.6	30M 30M	538	<div>Edit</div>
dino_telefon	Enable	10.0.110.8	30M 30M	209	<div>Edit</div>
galia_pc	Enable	10.0.110.11	30M 30M	211	<div>Edit</div>
peer_101	Enable	10.0.110.9	30M 30M	207	<div>Edit</div>
peer_215	Enable	10.0.110.2	30M 30M	323	<div>Edit</div>
ruslan_dom_pc	Enable	10.0.110.4	30M	377	<div>Edit</div>

Set the **IKEv2 Enabled** option to **YES** to keep the value of the **Save** button

Revision #9

Created 13 December 2022 09:51:13 by Ruslan

Updated 16 October 2023 08:58:31 by Yuliia Noha