

# Installation

[Order now](#) | [Download](#) | [FAQ](#)

It is important to follow instructions during the installation of VPN server software for several reasons:

- Following instructions ensures that the software is installed correctly and all required components are present. This can prevent errors and ensure that the software functions properly.
- Instructions often include important information about system requirements, compatibility, and potential issues that may arise during installation. By following these instructions, you can avoid encountering problems that could affect the performance or stability of the software.
- Instructions may also include important information about configuring and setting up the software, such as creating user accounts, assigning permissions, and establishing connections with other systems or devices. By following these instructions, you can ensure that the software is set up correctly and ready to use.
- Finally, following instructions during installation is a good practice that can help you avoid wasting time, effort, and resources. It can also help you avoid making mistakes that could be difficult or costly to fix later.

We suggest installing the software on a clean, freshly installed Debian/Ubuntu server.

We issue all commands after logging into the SSH terminal window as the root user.

Linux kernels less than 5.6 ( $\leq 5.5$ ) did not include Wireguard as a feature in the upstream kernel code. Adding Wireguard support to these (older) kernels is possible via additional modules. *Therefore, we suggest using the latest Debian or Ubuntu distributions. If you use the versions of the operating system specified in the requirements, you do not need to pay attention to this message.*

## Check kernel version

```
uname -sr
```

```
Linux 5.10.0-10-amd64
```

## 1. Update and Install the required packages

```
apt-get update  
apt-get upgrade  
reboot
```

```
apt-get update  
apt-get install wireguard wireguard-dkms wireguard-tools -y  
apt-get install strongswan strongswan-pki libstrongswan-extra-plugins -y  
apt-get install bind9 -y  
apt-get install iproute2 iptables -y
```

## 2. Download the latest version of the package

The latest version of software is always located at this address:

<https://download.puqcloud.com/cp/puqvpncp/>

## 3. Install the puqvpncp package

We carry out the installation by issuing the following command

```
wget https://download.puqcloud.com/cp/puqvpncp/puqvpncp_1.8.1_amd64.deb  
dpkg -i puqvpncp_1.8.1_amd64.deb
```

## 4. After installation, connect to your server via a web browser.

Point Your web browser to following Address: [http://YOUR\\_SERVER\\_IP:8098](http://YOUR_SERVER_IP:8098)

(replace the value of YOUR\_SERVER\_IP with your unique IP address)

**Username:** *admin*

**Password:** *admin*

You should see a similar dashboard view (depending on theme chosen and status).

On the screen below, we can see the status of the freshly installed server.

We can see when the panel reports that Wireguard, IKEv2 and DNS server are not installed. The firewall itself is installed, but not enabled. It is important to note that there are no elements in red.

**PUQVPNCP**? HELP ?admin (79.184.30.83)Logout

[Dashboard](#)[VPN servers](#)[VPN accounts](#)[Settings](#)[About us](#)

**Server Information**

Hostname:	real-1-4816
OS Name:	Ubuntu 20.04.5 LTS
Architecture:	amd64
CPU:	Common KVM processor
CPU Threads: 2 Load:	0.68, 0.45, 0.55
Memory:	1983 MiB Used: 86%
Timezone:	Etc/UTC

**PUQVPNCP**

Status:	OK
Version:	1.2
WireGuards:	0
VPN Accounts:	0/50
License:	Inactive license

[License](#)[Reload](#)

**WireGuard**

wireguard:	not installed
wireguard-dkms:	not installed
wireguard-tools:	not installed

[Configure](#)

**IKEv2**

strongswan:	not installed
Starter:	not running
Charon:	not running

[Configure](#)

**Firewall**

iptables:	1.8.4-3ubuntu2
iproute2:	5.5.0-1ubuntu1
Nat enabled:	not

[Configure](#)

**DNS server**

bind9:	not installed
Running:	not running

[Configure](#)

## 5. Installation of additional required packages.

To fully use the panel, you need to install a few additional packages.

### 5a. Installing WireGuard

Please click "Configuration" button in WireGuard box to be moved to installation WireGuard package.

**PUQVPNCP**? HELP ?admin (79.184.30.83)Logout

[Dashboard](#)[VPN servers](#)[VPN accounts](#)[Settings](#)[About us](#)

**Wireguard not installed**

wireguard:	not installed
wireguard-dkms:	not installed
wireguard-tools:	not installed

**Login to your server and run the following commands as root.**

```
apt-get update
apt-get install wireguard wireguard-dkms wireguard-tools -y
```

Please complete the package installation process according to the given instructions. Run these

commands as root in a terminal/CLI window

## 5b. Installing IKEv2

If you want to use the IKEv2 protocol, you need to install additional packages.

The installation of the IKEv2 protocol is not necessary for the operation of the system.

Please click "Configuration" button in IKEv2 box to be moved to installation mentioned package.

**PUQVPNCP**

? HELP ?admin (79.184.30.83)Logout

Dashboard

VPN servers

VPN accounts

Settings

About us

### IKEv2 not installed

strongswan:	not installed
Starter:	not running
Charon:	not running

apt-get update  
apt-get upgrade  
apt-get install strongswan strongswan-pki libstrongswan-extra-plugins -y

Please complete the package installation process according to the given instructions. Run these commands as root in a terminal/CLI window

## 5c. Installing DNS server

Please click "Configuration" button in DNS server box to be moved to installation Bind9

**PUQVPNCP**

? HELP ?admin (79.184.30.83)Logout

DashboardVPN serversVPN accountsSettingsAbout us

## BIND9 not installed

bind9:	not installed
Running:	not running

**Login to your server and run the following commands as root.**

```
apt-get update
apt-get install bind9 -y
```

package.

Please complete the package installation process according to the given instructions. Run these commands as root in a terminal/CLI window

## 6. Edit the configuration file if necessary.

If you need to change basic server parameters after installation, you can edit the configuration file and change parameters such as IP address, port number, SSL setting or changing the path to files. You must restart the server after making changes.

```
nano /etc/puqvpncp/puqvpncp.conf
```

## 7. Restart

For the server to start working properly, you must restart the server.

```
service puqvpncp restart
```

## 8. Status

To quickly know the status of a server service, just issue the following command

```
service puqvpncp status
```

After issuing this comment, you should see a similar result. Pay attention to the status information - the service is loaded and active.

● puqvpncp.service - PUQVPNCP

Loaded: loaded (/etc/systemd/system/puqvpncp.service; enabled; vendor preset: enabled)

Active: active (running) since Wed 2022-11-23 13:29:09 CET; 3h 0min ago

Main PID: 4180349 (puqvpncp)

Tasks: 9 (limit: 9509)

Memory: 31.0M

CPU: 1min 18.873s

CGroup: /system.slice/puqvpncp.service

└─4180349 /usr/sbin/puqvpncp

## 9. Additional settings after installation

Once you have finished installing the necessary packages, please proceed to the configuration section. For proper operation, additional configuration of, among others, a [firewall](#) is necessary.

---

Revision #33

Created 17 November 2022 13:18:27 by Ruslan

Updated 7 April 2024 01:43:57 by Ruslan