

Traffic Logging Config

[Order now](#) | [Download](#) | [FAQ](#)

Traffic Logging Get Config

Request Structure: `https://<puqvnpv>/api/v1/traffic_logging`

Method: `GET`

Cookie: `access_hash=<access_hash>`

Example:

```
curl \
-b
"access_hash=f3a4359ffc8c62629e1067c76df99cda7d64f4e82f8e24e6fa9569b9b48de5c58af8d53b4f444a70"
\
-X GET https://dev.softkeel.com/api/v1/traffic_logging
```

Response example:

```
{
  "error" : "",
  "msg" : {
    "enabled" : true,
    "enabled_influxdb" : true,
    "enabled_remote_syslog" : true,
    "established" : true,
    "incoming" : false,
    "influxdb_bucket" : "logs_puqvpncp",
    "influxdb_organization" : "PUQ sp. z o.o.",
    "influxdb_token" :
"xbU0AfUh0mPsP9Izviojd0TGLIyo8Io1PFW3DXK2VQDeoUEDDBXwEkJ36A6H2uDBIiW7DEVsG4TgGiUTq6rs1g==",
    "influxdb_url" : "http://77.87.125.208:8086",
```

```
"interface_in" : false,
"interface_out" : false,
"invalid" : false,
"len" : false,
"mark" : false,
"new" : false,
"related" : true,
"remote_syslog_server" : "77.87.125.208",
"remote_syslog_server_port" : 514,
"tos" : false,
"untracked" : false
},
"status" : "success"
}
```

Errors:

- Not authorized

Traffic Logging Edit Config

Request Structure: `https://<puqvpnpv>/api/v1/traffic_logging`

Cookie: `access_hash=<access_hash>`

Method: `PUT`

PUT data:

Not required:

```
"enabled" = 1| 0
"enabled_influxdb" = 1| 0
"enabled_remote_syslog" = 1| 0
"established" = 1| 0
"incoming" = 1| 0
"influxdb_bucket" = "<bucket_name>"
"influxdb_organization" = "<organization_name>"
"influxdb_token" = "<influxdb_token>"
```

```
"influxdb_url" = "influxdb_url"
"interface_in" = 1| 0
"interface_out" = 1| 0
"invalid" = 1| 0
"len" = 1| 0
"mark" = 1| 0
"new" = 1| 0
"related" = 1| 0
"remote_syslog_server" = <XXX. XXX. XXX. XXX>
"remote_syslog_server_port" = 1-65536,
"tos" = 1| 0
"untracked" = 1| 0
```

Example:

```
curl \
-b
"access_hash=f3a4359ffc8c62629e1067c76df99cda7d64f4e82f8e24e6fa9569b9b48de5c58af8d53b4f444a70"
\
-d "enabled=1&\
enabled_influxdb=1&\
enabled_remote_syslog=1&\
established=1&\
incoming=0&\
influxdb_bucket=logs_puqvpcp&\
influxdb_organization=PUQ sp. z o.o. &\
influxdb_token=xbU0AfUh0mPsP9Izviojd0pGLIyo8Io1PFW8DXKHVQDeoUEDDBXwEkJ36A6H2uDBIiW7DEVsG4TgGiUTq6rs1g=="
influxdb_url=http://77.87.125.208:8086&\
interface_in=0&\
interface_out=0&\
invalid=0&\
len=0&\
mark=0&\
new=0&\
related=1&\
remote_syslog_server=77.87.125.208&\
remote_syslog_server_port=514&\
tos=0&\
untracked=0" \
-X PUT https://dev.softkeel.com/api/v1/traffic_logging
```

Response example:

```
{
  "error" : "",
  "msg" : {
    "enabled" : true,
    "enabled_influxdb" : true,
    "enabled_remote_syslog" : true,
    "established" : true,
    "incoming" : false,
    "influxdb_bucket" : "logs_puqvpcp",
    "influxdb_organization" : "PUQ sp. z o.o.",
    "influxdb_token" :
    "xbU0AfUh0mPsP9Izviojd0pGLIyo8Io1PFW8DXKHVQDeoUEDDBXwEkJ36A6H2uDBIiW7DEVsG4TgGiUTq6rs1g==",
```

```
    "influxdb_url" : "http://77.87.125.208:8086",
    "interface_in" : false,
    "interface_out" : false,
    "invalid" : false,
    "len" : false,
    "mark" : false,
    "new" : false,
    "related" : true,
    "remote_syslog_server" : "77.87.125.208",
    "remote_syslog_server_port" : 514,
    "tos" : false,
    "untracked" : false
  },
  "status" : "success"
}
```

Errors:

- Not authorized
- Remote Syslog Server must be filled
- InfluxDB Telegraf not installed
- InfluxDB Url must be filled
- InfluxDB Token must be filled
- InfluxDB Bucket must be filled
- InfluxDB Organization must be filled
- At least one logging method must be enabled (Remote Syslog or/and InfluxDB)

Revision #7

Created 29 December 2022 12:54:49 by Ruslan

Updated 16 October 2023 10:13:43 by Yuliia Noha